## ADDENDUM NO. 2 INDIAN CREEK WRF EXPANSION TO 3 MGD HENRY COUNTY WATER AUTHORITY

Sealed bids will be received until 11:00 AM local time on October 4, 2016

This addendum hereby amends and/or modifies the Contract Documents, Detailed Specifications, and Drawings, as indicated, that have been issued for this project by Engineering Strategies, Inc. Additionally, questions received by the Engineer are answered at the end of this addendum. All bidders are subject to the provisions of this addendum and shall acknowledge receipt of this addendum on the bid form.

## 1 DETAILED SPECIFICATIONS

- A. Section 09900
  - 1. **ADD** the following to paragraph 2.2.B:
    - Concrete Floors Sever Chemical
      - a. System Type: Epoxy
      - b. Surface Preparation: SSPC-SP13/NACE 6, followed by abrasive blast
      - c. Prime Coat: Series 201 Epoxoprime, 6 to 12 mils DFT
      - d. Intermediate Coat: Series 282 Tneme-Glaze, 6 to 12 mils DFT
      - e. Finish Coat: Series 280 Tneme-Glaze, 6 to 12 mils DFT
      - f. Total DFT: 18 to 36 mils
      - g. Spread sand over prime coat to create rough non-slip surface.

## 2 DRAWINGS


- A. **REPLACE** the following drawings with the attached drawings.
  - 1. 45-S-3
  - 2. 95-S-2

## 3 QUESTIONS AND ANSWERS

- Q2-1: Will the owner furnish and pay for water and power for the commissioning and start-up testing? Membrane tanks will be filled and emptied several times during commissioning and will require potable water.
- A2-1: Yes, the owner will furnish and pay for water and power for the commissioning and start-up testing. This assumes all equipment is installed and powered through the new electrical system. During construction, the contractor is responsible for furnishing and paying for temporary utilities per Section 01510.
- Q2-2: Who is responsible for supplying the chemicals? Will tanks need to be topped off after commissioning and testing?
- A2-2: Owner will supply chemicals. Contractor shall coordinate with owner to have chemicals delivered after chemical facilities are installed and accepted for operation.

- Q2-3: Who will remove and refill fuel from the existing generator during the relocation? If it is the contractor's responsibility, then how many gallons?
- A2-3: Contractor shall be responsible for removing, transporting, and refilling generator fuel tanks. The fuel tank sizes are 4,500 gallons and 1,200 gallons.
- Q2-4: Will the contractor be responsible for the cost of any local permit fees?
- A2-4: Contractor is responsible for paying \$40 per disturbed acre to Georgia EPD. Any fees paid to Henry County for the land disturbance permit and/or building permit will be reimbursed to the contractor under the allowance included in the Bid Form. Reference Section 02115, paragraph 1.1.C. The fee to Georgia EPD must be paid prior to Henry County issuing the land disturbance permit.
- Q2-5: Will all pipe joints on buried pipelines, including the outfall, require restrained joints per section 15062, par. 2.1.5.b or can we use DIPRA thrust restraint design to determine how many joints require restraint?
- A2-5: All pressurized force mains shall be constructed with restrained joint pipe and fittings per General Civil Note 3. Gravity lines shall be restrained as per DIPRA thrust restrain design. The outfall line will generally be unrestrained except for what is required at bends and the last approximately 250 feet of line where it runs down a steep slope (reference Addendum No. 1).
- Q2-6: Specifications call for flange bolts for ductile iron fittings to be A307grB, but the note on 00-G-2 says all nut and bolts to be 316ss. Which is correct.
- A2-6: All hardware shall be Type 316 stainless steel. Reference Addendum No. 1.
- Q2-7: Sheet 00-C-40 shows a new 6" pipe being installed in the existing LAS Screen Structure. This detail is shown N.T.S. How deep is this structure? Can the structure be drained and liquids isolated by the owner prior to installing pipe? Will the structure need to be cleaned out prior to installing pipe?
- A2-7: The structure is approximately 26 feet deep. The structure has a gate that can be closed to shut off flow from the pond. Contractor shall provide pump to dewater the structure and clean out any debris that is in the bottom.
- Q2-8: The Room Finish Schedule finish schedule shows epoxy flooring to be installed in rooms 103, 104, and 105. Can you confirm that these rooms will receive the epoxy flooring and if so, can you provide specifications and/or detail?
- A2-8: Room 103 (MBR Process Electrical Room) does not need to be painted. Room 104 (MBR Process Sodium Hypochlorite Feed Room) and Room 105 (MBR Process Citric Acid Feed Room shall be painted using Coating System No. 27.
- Q2-9: Are CADD files available for earthwork? If not, are full scale .pdf's available?
- A2-9: Full scale .pdf's were provided in Addendum No. 1.
- Q2-10: Reference dwg. 40-S-2, detail C, note 4: Is the final post-tension force of 50-kips the total for all strands, or is it 50-kips per strand?
- A2-10: The final total post-tension force of all strands is 50 kip. The number of strands to achieve the final total post-tension force shall be per the post-tension system design engineer. A minimum of three (3) strands shall be provided to achieve the final post-tension force and shall be centered about the 1'-6" concrete encasement.

\*\* END OF ADDENDUM \*\*



NUMBER   ROUGH OPENING   MIDTH   HEIGHT   MAT'L   FIN   DETAILS   GLAZING   DESIGN   WIND   NOTES	SEE SCHED  ROUGH OPNG EQ EQ  EQ EQ  SEE SCHED  ROUGH OPNG EQ EQ EQ	Z No. 39.5 PROFESSIONAL B-24-16.
WC-02   12'-0"   4'-0"   B   ALUM   ANOD   -   -   -   1"   INSULATED   +38/-47	GLAZING B B B BS	NORD ROAD, SUITE 525  FORMARY BLVD., SUITE 210  BRIDA 32746  S22-0500  NO. 15-137  FORMARY BLVD., SUITE 525
GENERAL NOTES:  LIST OF ABBREVIATIONS:  K = KYNAR  ALUM = ALUMINUM  ANOD = ANODIZED	WINDOW TYPES  NTS  WINDOW TYPES	SI W. LAKE KE MARY, FL ONE: (407)-:  GINEERIN 3855 SHALLO'
	4" BRICK  LINTEL ANGLE  SOLIDER COURSE BRICK  8" OR 12" LINTEL BEAM  SOLIDER COURSE BRICK	DATE: AUGUST 2016 BATE AUGUST 2016 BATE E/T BATE E/T BATE BATE BATE BATE BATE BATE BATE BAT
	BRICK  SEALANT, TYP  SEALANT, TYP  INSECT SCREEN LOUVER  EXTERIOR MASONRY LOUVER HEAD  EXTERIOR MASONRY WINDOW HEAD	REVISION NO.2
ROOM FINISH SCHEDULE	DETAIL SCALE: NTS  DETAIL SCALE: NTS  DETAIL SCALE: NTS  DETAIL SCALE: NTS	ROJECT NUMBE ADDENDUM
101 STORAGE AREA	REFERENCE DWG.  YOU HAVE BRICK  4" BRICK  4" BRICK  8" CMU  GYP BOARD  SEALANT,  TYP	DSGN: DSM DRWN: DSM CHCK: JVS CHCK:
TRAINING ROOM   CONC   VT   GB   P   P   P   RB   AT	EXTERIOR MASONRY LOUVER JAMB  DETAIL SCALE: NTS  ALUM WINDOW  FRAME W/ 1" INSUL GLASS  EXTERIOR MASONRY WINDOW JAMB  DETAIL SCALE: NTS  ALUM WINDOW	TO 3 MGD
LIST OF ABBREVIATIONS:  C = CARPET  P = PAINT  AT = SUSPENDED ACOUSTIC TILE  CMU = EXPOSED CONC BLOCK  AP = ACOUSTICAL PANELS  CT = CERAMIC TILE  GB = GYPSUM BOARD  TB = TILE BACKER BOARD  RB = RUBBER BASE  PLY = T1-11 PLYWOOD	ND = WOOD N = NONE N = NONE N = NONE N = EXPOSED NES=UNDERSIDE OF XPOSED STRUCTURE  SOLIDER COURSE BRICK GROUT SOLID THRU-WALL FLASHING  THRU-WALL FLASHING  A" BRICK  BIRD AND INSECT SCREENS  BIRD AND INSECT SCREENS  SEALANT, TYP  FRAME W/ 1" INSUL GLASS  EXTEND SILL FLASHING OVER MASONRY SILL SET IN MASTIC  SOLIDER COURSE BRICK GROUT SOLID THRU-WALL FLASHING  INVERTED LINTEL BLOCK  INVERTED LINTEL BLOCK  THRU-WALL FLASHING  METAL FURRING STRIPS	CREEK WRF EXPANSION RY COUNTY WATER AUTH BUILDING SCHEDULES
	EXTERIOR MASONRY LOUVER SILL  DETAIL SCALE: NTS  A" BRICK  INVERTED LINTEL BLOCK  BLOCK  EXTERIOR MASONRY WINDOW SILL  DETAIL SCALE: NTS  TOTAL SCALE: NTS  A" BRICK  BRICK  BLOCK  BLOC	NDIAN CO SHEET NO
		95-S-2