



---

**GEOTECHNICAL DATA REPORT**

**FOR**

**SAN ANTONIO WATER SYSTEM  
W-1 LEON CREEK: HIGHWAY 151 TO HIGHWAY 90  
UPPER SEGMENT  
SAN ANTONIO, TEXAS**

---

Project No. ASA16-016-01  
January 21, 2019

Mr. Joseph Ortega, P.E.  
Pape-Dawson Engineers, Inc.  
2000 NW Loop 410  
San Antonio, TX 78213

P 210.699.9090  
F 210.699.6426  
TBPE Firm F-3257

**RE: Geotechnical Data Report  
SAWS - W-1 Leon Creek Highway 90 to Highway 151  
Upper Segment  
San Antonio, Texas**


Dear Mr. Ortega:

Raba Kistner Consultants, Inc. (RKCI) is pleased to submit the report of our Geotechnical Data Report for the above-referenced project. This study was performed in accordance with RKCI Proposal No. PSA15-168-00, dated October 29, 2015 and the amended agreement dated September 19, 2018. The purpose of this study was to drill borings along the proposed upper segment alignment, perform laboratory testing to evaluate and characterize subsurface conditions, and present our findings in a Geotechnical Data Report.

We appreciate the opportunity to be of service to you on this project. Please call the undersigned should you have any questions about the information presented in this data report.

Very truly yours,

**RABA KISTNER CONSULTANTS, INC.**



Eric J. Neuner, P.E.  
Associate | Manager, San Antonio Engineering

1/21/2019

SH/EJN/kv

Attachments

Copies Submitted: Above (Electronic Copy)



12821 W. Golden Lane  
San Antonio, TX 78249  
P.O. Box 690287  
San Antonio, TX 78269-0287  
www.rkci.com

Project No. ASA16-016-01  
January 21, 2019

Mr. Joseph Ortega, P.E.  
Pape-Dawson Engineers, Inc.  
2000 NW Loop 410  
San Antonio, TX 78213

P 210.699.9090  
F 210.699.6426  
TBPE Firm F-3257

**RE: Geotechnical Data Report  
SAWS - W-1 Leon Creek Highway 90 to Highway 151  
Upper Segment  
San Antonio, Texas**

Dear Mr. Ortega:

Raba Kistner Consultants, Inc. (RKCI) is pleased to submit the report of our Geotechnical Data Report for the above-referenced project. This study was performed in accordance with RKCI Proposal No. PSA15-168-00, dated October 29, 2015 and the amended agreement dated September 19, 2018. The purpose of this study was to drill borings along the proposed upper segment alignment, perform laboratory testing to evaluate and characterize subsurface conditions, and present our findings in a Geotechnical Data Report.

We appreciate the opportunity to be of service to you on this project. Please call the undersigned should you have any questions about the information presented in this data report.

Very truly yours,

**RABA KISTNER CONSULTANTS, INC.**

Eric J. Neuner, P.E.  
Associate | Manager, San Antonio Engineering

SH/EJN/kv

Attachments

Copies Submitted: Above (Electronic Copy)

**GEOTECHNICAL DATA REPORT**

For

**SAN ANTONIO WATER SYSTEM  
WR-1 LEON CREEK: HIGHWAY 151 TO HIGHWAY 90  
UPPER SEGMENT  
SAN ANTONIO, TEXAS**

Prepared for

**PAPE-DAWSON ENGINEERS, INC.**  
San Antonio, Texas

Prepared by

**RABA KISTNER CONSULTANTS, INC.**  
San Antonio, Texas

**PROJECT NO. ASA16-016-01**

January 21, 2019

**TABLE OF CONTENTS**

**INTRODUCTION**..... 1  
**PROJECT DESCRIPTION** ..... 1  
**LIMITATIONS** ..... 1  
**BORINGS AND LABORATORY TESTS** ..... 1  
    CORROSIVITY TESTING ..... 2  
**GENERAL SITE CONDITIONS** ..... 3  
    SITE DESCRIPTION ..... 3  
    GEOLOGY ..... 3  
    STRATIGRAPHY ..... 3  
    GROUNDWATER ..... 4

**ATTACHMENTS**

The following figures are attached and complete this report:

Boring Location Map ..... Figure 1  
Logs of Borings ..... Figures 2 to 9  
Key to Terms and Symbols ..... Figure 10  
Results of Soil Analyses ..... Figure 11  
Important Information About Your Geotechnical Engineering Report

## **INTRODUCTION**

RKCI has completed the authorized subsurface exploration for the Upper Segment of the proposed W-1 Leon Creek wastewater pipeline project, as illustrated on Figure 1. The overall project spans approximately from Loop 410 to US Highway 90 in San Antonio, Texas (approximately 4 miles). This data report briefly describes the procedures utilized during this study and presents our findings for the upper segment to aid in new wastewater line design and construction.

## **PROJECT DESCRIPTION**

Based on the project information and the preliminary alignment drawing provided to us by Pape-Dawson Engineers, Inc., we understand that the wastewater line will generally start southeast of Loop 410 and terminate near U.S. 90 Access Road, in San Antonio, Texas. The Upper Segment alignment generally extends north and west of Leon Creek and terminates near South Brownleaf Drive in San Antonio, Texas. The majority of the construction is anticipated to be open cut with bore and jack sites beneath paved roads, creeks, and possibly other crossings.

## **LIMITATIONS**

This geotechnical data report has been prepared in accordance with accepted Geotechnical Engineering practices in the region of south/central Texas and for the use of Pape-Dawson Engineers, Inc. (CLIENT) and its representatives for design purposes. This report may not contain sufficient information for purposes of other parties or other uses. This report is not intended for use in determining construction means and methods.

The data submitted in this report are based on 8 borings drilled along the proposed alignment, our understanding of the project information provided to us. If the project information described in this report is incorrect, is altered, or if new information is available, we should be retained to review and modify our findings as needed.

This data report may not reflect the actual variations of the subsurface conditions across the site. The nature and extent of variations across the site may not become evident until construction commences. The construction process itself may also alter subsurface conditions. Our scope does not include an environmental assessment of the air, soil, rock, or water conditions either on or adjacent to the site. No environmental opinions are presented in this report.

## **BORINGS AND LABORATORY TESTS**

Subsurface conditions at the site were evaluated by 8 borings drilled at the locations shown on the Boring Location Map, Figure 1. These locations are approximate and distances were measured using a hand-held, recreational-grade GPS locator. Ground surface elevations were estimated from the topography depicted on the preliminary alignment drawing provided by Pape-Dawson Engineers, Inc. The estimated ground surface elevation at each boring location and the boring bottom elevation are summarized in the following table.

**Boring Summary – Upper Segment**

<b>Boring No.</b>	<b>Estimated Ground Surface Elevation (ft, MSL)</b>	<b>Estimated Boring Bottom Elevation (ft, MSL)</b>
B-1	724.6	698.6
B-2	716.0	696.0
B-3	713.2	693.2
B-4	710.5	693.0
B-5	712.0	692.0
B-6	710.5	690.5
B-7	710.5	689.5
B-8	704.0	687.0

Borings were drilled using a truck-mounted drilling rig. During drilling operations, Split-Spoon (with Standard Penetration Test), Shelby Tube, and Grab Samples were collected. Each sample was visually classified in the laboratory by a member of our geotechnical engineering staff. The geotechnical index properties of the strata were evaluated by natural moisture content, Atterberg limits, percent passing a No. 200 sieve, and unconfined compressive strength tests. In addition, analytical testing was performed on select samples to evaluate the soil corrosivity (including pH, electrical resistivity, and sulfate and chloride content determinations). The results are presented in the following section.

The laboratory test results are presented in graphical or numerical form on the boring logs illustrated on Figures 2 through 9. A key to classification terms and symbols used on the logs is presented on Figure 10. The results of the laboratory and field testing are also tabulated on Figure 11 for ease of reference.

Standard Penetration Test results are noted as “blows per ft” on the boring logs and Figure 11, where “blows per ft” refers to the number of blows by a falling hammer required for 1 ft of penetration into the soil/weak rock (N-value). Where hard or dense materials were encountered, the tests were terminated at 50 blows even if one foot of penetration had not been achieved. When all 50 blows fall within the first 6 in. (seating blows), refusal “ref” for 6 in. or less will be noted on the boring logs and on Figure 11.

**CORROSIVITY TESTING**

The corrosivity characteristics of the select soil samples were evaluated using pH, resistivity, sulfate content, and chloride content tests. These tests were performed on selected sample specimens obtained from the subsurface materials. Results are summarized in the following table.

Corrosivity Testing Summary					
Boring	Composite Sample Depth (ft)	Resistivity (Ohm-cm)	pH	Sulfate Content (ppm)	Chloride Content (ppm)
B-1	13-24.5	1,166	9.2	140	8.2
B-2	6.5-20	*	9.3	1,010	17.8
B-3	15-20	542	9.0	570	13.2
B-4	11-13	3,087	10.0	208	27.8
B-5	14-16	3,842	10.1	161	30.6
B-6	8.5-20	*	9.6	990	26.3
B-7	8.5-20.5	*	9.1	808	23.6
B-8	8.5-17	*	10.1	181	12.9

\*Not enough sample to perform laboratory test.

## GENERAL SITE CONDITIONS

### SITE DESCRIPTION

The proposed upper segment of the wastewater line site extends across developed and undeveloped areas. There are a significant number of buried structures and existing utilities in the vicinity of these project alignments; it is also possible that abandoned foundations, structures, and utilities are present which were not encountered during field operations. The presence of buried structures (old utility structures, pavements, brick, debris, abandoned utilities, etc.) should be anticipated. The roadway crossings included in our exploration in this portion of the project site are listed below:

- West Commerce Street
- Highway 151
- Pinn Road

### GEOLOGY

A review of the *Geologic Atlas of Texas, San Antonio Sheet*, indicates that this site is naturally underlain with soils of the Fluvial Terrace Deposit (Borings B-1 through B-8). Fluvial terrace deposits are stream bed deposits typically consisting of clays, sands, silts, and gravels. Such deposits can contain point bars, cutbanks, oxbows, and abandoned channel segments associated with variations in stream bed activity. As a result, soil profiles in terrace deposit areas may vary greatly over relatively short vertical and horizontal distances, and may contain water-bearing strata.

### STRATIGRAPHY

The boring logs should be consulted for specific stratigraphic information at each individual location. Each stratum has been designated by grouping materials that possess similar physical and engineering characteristics. The boring logs should be consulted for more specific stratigraphic information. Unless noted on the boring logs, the lines designating the changes between various strata represent approximate boundaries. The transition between materials may be gradual or may occur between recovered samples. It should be noted that there can be variations from that shown or described on the boring logs.



The boring logs and related information depict subsurface conditions only at the specific locations and times where sampling was conducted. The passage of time may result in changes in conditions, interpreted to exist, at or between the locations where sampling was conducted.

**GROUNDWATER**

During drilling, groundwater was encountered in Borings B-1 through B-6, and B-8 at depths ranging from approximately 2.5 ft to 15 ft below the existing ground surface and our boring logs should be reviewed for specific information. The observed groundwater is summarized in the following table.

Boring No.	Estimated Ground Surface Elevation (ft, MSL)	Approximate Elevation (ft, MSL)	
		Seepage <sup>(1)</sup>	Groundwater <sup>(2)</sup>
B-1	724.6	710.6	711.9
B-2	716.0	Not Observed	713.1
B-3	713.2	708.2	698.4
B-4	710.5	708.0	708.0
B-5	712.0	708.5	708.5
B-6	710.5	703.0	703.2
B-8	704.0	692.0	695.2

<sup>1)</sup>noted by the logger during drilling

<sup>2)</sup>measured upon termination of the boring

The remaining borings remained dry throughout the exploration phase. Groundwater levels may not have stabilized, particularly in less permeable cohesive soil, prior to backfilling. Consequently, the indicated groundwater levels, or lack thereof, may not represent present or future levels. It is possible for groundwater to exist beneath this site at shallow depths on a transient basis following periods of precipitation and within permeable strata or fills. Fluctuations in groundwater levels occur due to variation in rainfall, surface water run-off, the stage of Leon Creek, or other factors not evident at the time of exploration. The construction process itself may also cause variations in the groundwater level.

\* \* \* \* \*

# ATTACHMENTS



**LEGEND**

- BORING
- PROPOSED ALIGNMENT
- STREAM

0 250 500 1,000  
FEET  
1 INCH = 1,000 FEET

**50 YEARS** **RABA KISTNER**  
Building Better Tomorrows

12821 West Golden Lane  
San Antonio, Texas 78249  
(210)699-9090 TEL  
(210)699-6426 FAX  
[www.rkci.com](http://www.rkci.com)  
TBPE Firm Number 3257

SOURCE: Aerial Photography Obtained from the City of San Antonio (COSA) - 2013

**BORING LOCATION MAP**  
SAWS W-1 LEON CREEK HWY 90 TO HWY 151  
UPPER SEGMENT  
SAN ANTONIO, TEXAS

**BEXAR COUNTY**

PROJECT No.:  
ASA16-016-00

ISSUE DATE:	01/18/2019
DRAWN BY:	CCL
CHECKED BY:	IM
REVIEWED BY:	EJN

**FIGURE**  
**1**

NOTE: This Drawing is Provided for Illustration Only, May Not be to Scale and is Not Suitable for Design or Construction Purposes

**LOG OF BORING NO. B-1**  
 SAWS W-1 Leon Creek Hwy 90 to Hwy 151  
 Upper Segment  
 San Antonio, Texas



**DRILLING METHOD:** Straight Flight Auger

**LOCATION:** N 29.44427; W 98.63338

DEPTH, FT	SYMBOL	SAMPLES	DESCRIPTION OF MATERIAL	BLOWS PER FT	UNIT DRY WEIGHT, pcf	SHEAR STRENGTH, TONS/FT <sup>2</sup>				PLASTICITY INDEX	% -200
						0.5	1.0	1.5	2.0		
SURFACE ELEVATION: 724.58 ft											
3			CLAY, Soft, Dark Brown, with gravel and trace sand	3							
5			SAND, Clayey, Loose, Tan, with calcareous deposit and gravel	29							15
12				4							
15			CLAY, Stiff, Tan, with gray mottling - DRILLER'S NOTE: WATER encountered at 14 ft	107							31
15			MARL, Hard, Tan	ref/3"							
18				ref/2"							
20				ref/1"							
22				ref/1"							
24				ref/1"							
25			Boring Terminated								

NOTE: THESE LOGS SHOULD NOT BE USED SEPARATELY FROM THE PROJECT REPORT

<b>DEPTH DRILLED:</b> 26.0 ft	<b>DEPTH TO WATER:</b> 12.7 ft	<b>PROJ. No.:</b> ASA16-016-00
<b>DATE DRILLED:</b> 8/16/2016	<b>DATE MEASURED:</b> 8/16/2016	<b>FIGURE:</b> 2

**LOG OF BORING NO. B-2**  
 SAWS W-1 Leon Creek Hwy 90 to Hwy 151  
 Upper Segment  
 San Antonio, Texas



**DRILLING METHOD:** Straight Flight Auger

**LOCATION:** N 29.43712; W 98.62943

DEPTH, FT	SYMBOL	SAMPLES	DESCRIPTION OF MATERIAL	BLOWS PER FT	UNIT DRY WEIGHT, pcf	SHEAR STRENGTH, TONS/FT <sup>2</sup>			PLASTICITY INDEX	% -200
						0.5	1.0	1.5		
			SURFACE ELEVATION: 716 ft							
			CLAY, Firm, Dark Brown, with gravel	5						
			MARL, Hard, Tan	50/6"						
5			ref/2"							
			SHALE, Hard, Gray	ref/3"						
			ref/3"						9	
10			ref/2"							
			ref/2"							
15			ref/2"							
			50/6"						31	
20			50/10"							
			Boring Terminated							
25										
30										
35										
<b>DEPTH DRILLED:</b> 20.0 ft			<b>DEPTH TO WATER:</b> 2.9 ft			<b>PROJ. No.:</b> ASA16-016-00				
<b>DATE DRILLED:</b> 8/16/2016			<b>DATE MEASURED:</b> 8/16/2016			<b>FIGURE:</b> 3				

NOTE: THESE LOGS SHOULD NOT BE USED SEPARATELY FROM THE PROJECT REPORT

**LOG OF BORING NO. B-3**  
 SAWS W-1 Leon Creek Hwy 90 to Hwy 151  
 Upper Segment  
 San Antonio, Texas



**DRILLING METHOD:** Straight Flight Auger

**LOCATION:** N 29.43914; W 98.62958

DEPTH, FT	SYMBOL	SAMPLES	DESCRIPTION OF MATERIAL	BLOWS PER FT	UNIT DRY WEIGHT, pcf	SHEAR STRENGTH, TONS/FT <sup>2</sup>		PLASTICITY INDEX	% -200
						0.5 1.0 1.5 2.0 2.5 3.0 3.5 4.0	PLASTIC LIMIT WATER CONTENT LIQUID LIMIT		
			SURFACE ELEVATION: 713.17 ft						
			POSSIBLE FILL: GRAVEL, Clayey, Loose to Medium Dense, Dark Brown, with sand	8		●			33
5			GRAVEL, Medium Dense to Very Dense, Tan with clay and sand - DRILLER'S NOTE: WATER encountered at 5 ft	16		●			
			MARL, Hard, Tan	22		●			
				ref/6"		●			
				ref/5"		●			
10				ref/4"		●	×		29
			SHALE, Hard, Gray	39		●			
15				50/11"		●			
				50/10"		●			
20				50/8"		●	×		31
			Boring Terminated						

NOTE: THESE LOGS SHOULD NOT BE USED SEPARATELY FROM THE PROJECT REPORT

<b>DEPTH DRILLED:</b> 20.0 ft	<b>DEPTH TO WATER:</b> 14.8 ft	<b>PROJ. No.:</b> ASA16-016-00
<b>DATE DRILLED:</b> 9/2/2016	<b>DATE MEASURED:</b> 9/2/2016	<b>FIGURE:</b> 4

**LOG OF BORING NO. B-4**  
 SAWS W-1 Leon Creek Hwy 90 to Hwy 151  
 Upper Segment  
 San Antonio, Texas



**DRILLING METHOD:** Straight Flight Auger

**LOCATION:** N 29.43503; W 98.62828

DEPTH, FT	SYMBOL	SAMPLES	DESCRIPTION OF MATERIAL	BLOWS PER FT	UNIT DRY WEIGHT, pcf	SHEAR STRENGTH, TONS/FT <sup>2</sup>				PLASTICITY INDEX	% -200				
						0.5	1.0	1.5	2.0			2.5	3.0	3.5	4.0
			SURFACE ELEVATION: 710.5 ft			10	20	30	40	50	60	70	80		
			POSSIBLE FILL: GRAVEL, Clayey, Medium Dense, Dark Brown, with sand	10											
			- DRILLER'S NOTE: WATER encountered at 2-1/2 ft	17											17
5			SHALE, Hard, Gray	ref/3"											
				ref/3"											
				ref/4"											
10				ref/3"											
				ref/2"											9
15				ref/2"											
				ref/1"											
			Boring Terminated												
20															
25															
30															
35															
<b>DEPTH DRILLED:</b>			17.5 ft	<b>DEPTH TO WATER:</b>			2.5 ft	<b>PROJ. No.:</b>			ASA16-016-00				
<b>DATE DRILLED:</b>			10/14/2016	<b>DATE MEASURED:</b>			10/14/2016	<b>FIGURE:</b>			5				

NOTE: THESE LOGS SHOULD NOT BE USED SEPARATELY FROM THE PROJECT REPORT

**LOG OF BORING NO. B-5**  
 SAWS W-1 Leon Creek Hwy 90 to Hwy 151  
 Upper Segment  
 San Antonio, Texas



**DRILLING METHOD:** Straight Flight Auger

**LOCATION:** N 29.43412; W 98.62700

DEPTH, FT	SYMBOL	SAMPLES	DESCRIPTION OF MATERIAL	BLOWS PER FT	UNIT DRY WEIGHT, pcf	SHEAR STRENGTH, TONS/FT <sup>2</sup>						PLASTICITY INDEX	% -200
						0.5	1.0	1.5	2.0	2.5	3.0		
			SURFACE ELEVATION: 712 ft										
			POSSIBLE FILL: GRAVEL, Clayey, Dense To Medium Dense, Dark Brown, with sand	34									
			-DRILLER'S NOTE: WATER encountered at 3-1/2 ft	28									8
5			SHALE, Hard, Gray	50/3"									8
				ref/3"									
				ref/4"									
10				ref/4"									
				ref/4"									
				ref/4"									
15				ref/3"									
				ref/2"									
				ref/1"									
20			Boring Terminated										
25													
30													
35													
<b>DEPTH DRILLED:</b>		20.0 ft		<b>DEPTH TO WATER:</b>		3.5 ft		<b>PROJ. No.:</b>		ASA16-016-00			
<b>DATE DRILLED:</b>		10/14/2016		<b>DATE MEASURED:</b>		10/14/2016		<b>FIGURE:</b>		6			

NOTE: THESE LOGS SHOULD NOT BE USED SEPARATELY FROM THE PROJECT REPORT



**LOG OF BORING NO. B-6**  
 SAWS W-1 Leon Creek Hwy 90 to Hwy 151  
 Upper Segment  
 San Antonio, Texas



**DRILLING METHOD:** Straight Flight Auger

**LOCATION:** N 29.43200; W 98.62325

DEPTH, FT	SYMBOL	SAMPLES	DESCRIPTION OF MATERIAL	BLOWS PER FT	UNIT DRY WEIGHT, pcf	SHEAR STRENGTH, TONS/FT <sup>2</sup>				PLASTICITY INDEX	% -200	
						0.5	1.0	1.5	2.0			2.5
			SURFACE ELEVATION: 710.5 ft									
			CLAY, Stiff, Dark Brown, with gravel	7								
			CLAY, Sandy, Stiff, Tan, with gravel	10							24	
5				11								
			GRAVEL, Clayey, Medium Dense, Tan - DRILLER'S NOTE: WATER encountered at 7-1/2 ft	13							9	
			SHALE, Hard, Gray	50/4"								
10				ref/3"							8	
				ref/2"								
				ref/2"								
15				ref/2"								
				ref/2"								
				ref/2"								
20			Boring Terminated									
25												
30												
35												
<b>DEPTH DRILLED:</b> 20.0 ft			<b>DEPTH TO WATER:</b> 7.3 ft			<b>PROJ. No.:</b> ASA16-016-00						
<b>DATE DRILLED:</b> 8/16/2016			<b>DATE MEASURED:</b> 8/16/2016			<b>FIGURE:</b> 7						

NOTE: THESE LOGS SHOULD NOT BE USED SEPARATELY FROM THE PROJECT REPORT

**LOG OF BORING NO. B-7**  
 SAWS W-1 Leon Creek Hwy 90 to Hwy 151  
 Upper Segment  
 San Antonio, Texas



**DRILLING METHOD:** Straight Flight Auger

**LOCATION:** N 29.43123; W 98.62104

DEPTH, FT	SYMBOL	SAMPLES	DESCRIPTION OF MATERIAL	BLOWS PER FT	UNIT DRY WEIGHT, pcf	SHEAR STRENGTH, TONS/FT <sup>2</sup>				PLASTICITY INDEX	% -200	
						0.5	1.0	1.5	2.0			2.5
			SURFACE ELEVATION: 710.5 ft									
			POSSIBLE FILL: CLAY, gravelly, Stiff to Hard, Dark Brown	7							28	
5			- with gravel from 3 ft to 5-1/2 ft	30								
				14							18	
				18								
			MARL, Hard, Tan	ref/3"								
10			SHALE, Hard, Gray	ref/2"							14	
				ref/1"								
				ref/1"								
15				ref/1"								
				ref/1"								
				ref/1"								
20				ref/1"								
				ref/2"							10	
			Boring Terminated									
25												
30												
35												
<b>DEPTH DRILLED:</b> 21.0 ft			<b>DEPTH TO WATER:</b> DRY			<b>PROJ. No.:</b> ASA16-016-00						
<b>DATE DRILLED:</b> 8/17/2016			<b>DATE MEASURED:</b> 8/17/2016			<b>FIGURE:</b> 8						

NOTE: THESE LOGS SHOULD NOT BE USED SEPARATELY FROM THE PROJECT REPORT

**LOG OF BORING NO. B-8**  
 SAWS W-1 Leon Creek Hwy 90 to Hwy 151  
 Upper Segment  
 San Antonio, Texas



**DRILLING METHOD:** Straight Flight Auger

**LOCATION:** N 29.42924; W 98.61786


DEPTH, FT	SYMBOL	SAMPLES	DESCRIPTION OF MATERIAL	BLOWS PER FT	UNIT DRY WEIGHT, pcf	SHEAR STRENGTH, TONS/FT <sup>2</sup>							PLASTICITY INDEX	% -200	
						0.5	1.0	1.5	2.0	2.5	3.0	3.5			4.0
			SURFACE ELEVATION: 704 ft												
5			POSSIBLE FILL: CLAY, Very Stiff to Hard, Dark Brown - with gravel and sand from 1 ft to 3-1/2 ft	24											
			CLAY, Very Stiff to Hard, Tan, with gravel and calcareous deposit	30											
				28											
				31									15		
10			GRAVEL, Medium Dense to Very Dense, Tan with clay and sand	21										15	
				14											
			- DRILLER'S NOTE: WATER encountered at 12 ft	50/8"										24	
15			SHALE, Hard, Gray	ref/2"											
				ref/1"											
			Boring Terminated												
20															
25															
30															
35															
<b>DEPTH DRILLED:</b>		17.0 ft		<b>DEPTH TO WATER:</b>		8.8 ft		<b>PROJ. No.:</b>		ASA16-016-00					
<b>DATE DRILLED:</b>		8/17/2016		<b>DATE MEASURED:</b>		8/17/2016		<b>FIGURE:</b>		9					

NOTE: THESE LOGS SHOULD NOT BE USED SEPARATELY FROM THE PROJECT REPORT


# KEY TO TERMS AND SYMBOLS

## MATERIAL TYPES


### SOIL TERMS




### ROCK TERMS




### OTHER




## WELL CONSTRUCTION AND PLUGGING MATERIALS



## SAMPLE TYPES



## STRENGTH TEST TYPES



NOTE: VALUES SYMBOLIZED ON BORING LOGS REPRESENT SHEAR STRENGTHS UNLESS OTHERWISE NOTED

PROJECT NO. ASA16-016-00

## KEY TO TERMS AND SYMBOLS (CONT'D)

### TERMINOLOGY

Terms used in this report to describe soils with regard to their consistency or conditions are in general accordance with the discussion presented in Article 45 of SOILS MECHANICS IN ENGINEERING PRACTICE, Terzaghi and Peck, John Wiley & Sons, Inc., 1967, using the most reliable information available from the field and laboratory investigations. Terms used for describing soils according to their texture or grain size distribution are in accordance with the UNIFIED SOIL CLASSIFICATION SYSTEM, as described in American Society for Testing and Materials D2487-06 and D2488-00, Volume 04.08, Soil and Rock; Dimension Stone; Geosynthetics; 2005.

The depths shown on the boring logs are not exact, and have been estimated to the nearest half-foot. Depth measurements may be presented in a manner that implies greater precision in depth measurement, i.e 6.71 meters. The reader should understand and interpret this information only within the stated half-foot tolerance on depth measurements.

#### RELATIVE DENSITY

#### COHESIVE STRENGTH

#### PLASTICITY

<u>Penetration Resistance Blows per ft</u>	<u>Relative Density</u>	<u>Resistance Blows per ft</u>	<u>Consistency</u>	<u>Cohesion TSF</u>	<u>Plasticity Index</u>	<u>Degree of Plasticity</u>
0 - 4	Very Loose	0 - 2	Very Soft	0 - 0.125	0 - 5	None
4 - 10	Loose	2 - 4	Soft	0.125 - 0.25	5 - 10	Low
10 - 30	Medium Dense	4 - 8	Firm	0.25 - 0.5	10 - 20	Moderate
30 - 50	Dense	8 - 15	Stiff	0.5 - 1.0	20 - 40	Plastic
> 50	Very Dense	15 - 30	Very Stiff	1.0 - 2.0	> 40	Highly Plastic
		> 30	Hard	> 2.0		

### ABBREVIATIONS

B = Benzene	Qam, Qas, Qal = Quaternary Alluvium	Kef = Eagle Ford Shale
T = Toluene	Qat = Low Terrace Deposits	Kbu = Buda Limestone
E = Ethylbenzene	Qbc = Beaumont Formation	Kdr = Del Rio Clay
X = Total Xylenes	Qt = Fluvial Terrace Deposits	Kft = Fort Terrett Member
BTEX = Total BTEX	Qao = Seymour Formation	Kgt = Georgetown Formation
TPH = Total Petroleum Hydrocarbons	Qle = Leona Formation	Kep = Person Formation
ND = Not Detected	Q-Tu = Uvalde Gravel	Kek = Kainer Formation
NA = Not Analyzed	Ewi = Wilcox Formation	Kes = Escondido Formation
NR = Not Recorded/No Recovery	Emi = Midway Group	Kew = Walnut Formation
OVA = Organic Vapor Analyzer	Mc = Catahoula Formation	Kgr = Glen Rose Formation
ppm = Parts Per Million	EI = Laredo Formation	Kgru = Upper Glen Rose Formation
	Kknm = Navarro Group and Marlbrook Marl	Kgrl = Lower Glen Rose Formation
	Kpg = Pecan Gap Chalk	Kh = Hensell Sand
	Kau = Austin Chalk	

PROJECT NO. ASA16-016-00

# KEY TO TERMS AND SYMBOLS (CONT'D)

## TERMINOLOGY

### SOIL STRUCTURE

Slickensided	Having planes of weakness that appear slick and glossy.
Fissured	Containing shrinkage or relief cracks, often filled with fine sand or silt; usually more or less vertical.
Pocket	Inclusion of material of different texture that is smaller than the diameter of the sample.
Parting	Inclusion less than 1/8 inch thick extending through the sample.
Seam	Inclusion 1/8 inch to 3 inches thick extending through the sample.
Layer	Inclusion greater than 3 inches thick extending through the sample.
Laminated	Soil sample composed of alternating partings or seams of different soil type.
Interlayered	Soil sample composed of alternating layers of different soil type.
Intermixed	Soil sample composed of pockets of different soil type and layered or laminated structure is not evident.
Calcareous	Having appreciable quantities of carbonate.
Carbonate	Having more than 50% carbonate content.

## SAMPLING METHODS

### RELATIVELY UNDISTURBED SAMPLING

Cohesive soil samples are to be collected using three-inch thin-walled tubes in general accordance with the Standard Practice for Thin-Walled Tube Sampling of Soils (ASTM D1587) and granular soil samples are to be collected using two-inch split-barrel samplers in general accordance with the Standard Method for Penetration Test and Split-Barrel Sampling of Soils (ASTM D1586). Cohesive soil samples may be extruded on-site when appropriate handling and storage techniques maintain sample integrity and moisture content.

### STANDARD PENETRATION TEST (SPT)

A 2-in.-OD, 1-3/8-in.-ID split spoon sampler is driven 1.5 ft into undisturbed soil with a 140-pound hammer free falling 30 in. After the sampler is seated 6 in. into undisturbed soil, the number of blows required to drive the sampler the last 12 in. is the Standard Penetration Resistance or "N" value, which is recorded as blows per foot as described below.

### SPLIT-BARREL SAMPLER DRIVING RECORD

<u>Blows Per Foot</u>	<u>Description</u>
25 .....	25 blows drove sampler 12 inches, after initial 6 inches of seating.
50/7" .....	50 blows drove sampler 7 inches, after initial 6 inches of seating.
Ref/3" .....	50 blows drove sampler 3 inches during initial 6-inch seating interval.

NOTE: To avoid damage to sampling tools, driving is limited to 50 blows during or after seating interval.

# RESULTS OF SOIL SAMPLE ANALYSES

PROJECT NAME: SAWS W-1 Leon Creek Hwy 90 to Hwy 151  
Upper Segment  
San Antonio, Texas

FILE NAME: ASA16-016-00 FOR DATA REPORT - NO INVERT ELEVATION.GPJ

1/4/2019

Boring No.	Sample Depth (ft)	Blows per ft	Water Content (%)	Liquid Limit	Plastic Limit	Plasticity Index	USCS	Dry Unit Weight (pcf)	% -200 Sieve	Shear Strength (tsf)	Strength Test
B-1	0.0 to 1.5	3	12								
	2.5 to 4.0	29	9								
	4.5 to 6.0	25	3						15		
	6.5 to 8.0	12	5								
	8.5 to 10.0	4	20								
	13.0 to 14.0		18	48	17	31		107		1.94	UC
	14.0 to 14.5										
	15.0 to 15.3	ref/3"	10								
	16.5 to 17.0										
	17.0 to 17.2	ref/2"	9								
	18.5 to 19.0										
	19.0 to 19.1	ref/1"	10								
	20.5 to 21.0										
	21.0 to 21.1	ref/1"	8								
	22.5 to 23.0										
23.0 to 23.1	ref/1"	4									
B-2	0.0 to 1.5	5	19								
	2.5 to 3.5	50/6"	11								
	4.5 to 4.7	ref/2"	8								
	6.5 to 6.8	ref/3"	13								
	8.5 to 8.8	ref/3"	14	23	14	9					
	10.5 to 10.7	ref/2"	14								
	12.5 to 12.7	ref/2"	15								
	14.5 to 14.7	ref/2"	20								
16.5 to 17.5	50/6"	20	54	23	31						
18.5 to 19.9	50/10"	23									
B-3	0.0 to 1.5	8	6						33		
	2.5 to 4.0	16	10								
	4.5 to 6.0	22	9								
	6.5 to 7.0	ref/6"	12								
	8.5 to 8.9	ref/5"	16								
	10.5 to 10.8	ref/4"	19	54	25	29					
	12.5 to 14.0	39	24								
	14.5 to 15.9	50/11"	24								
16.5 to 17.9	50/10"	25									
18.5 to 19.7	50/8"	24	59	28	31						
B-4	0.0 to 1.5	10	9								
	2.5 to 4.0	17	15						17		
	4.5 to 4.7	ref/3"	10								

PP = Pocket Penetrometer TV = Torvane UC = Unconfined Compression FV = Field Vane UU = Unconsolidated Undrained Triaxial

CU = Consolidated Undrained Triaxial

PROJECT NO. ASA16-016-00

**RABAKISTNER**

FIGURE 11a

# RESULTS OF SOIL SAMPLE ANALYSES

PROJECT NAME: SAWS W-1 Leon Creek Hwy 90 to Hwy 151  
Upper Segment  
San Antonio, Texas

FILE NAME: ASA16-016-00 FOR DATA REPORT - NO INVERT ELEVATION.GPJ

1/4/2019

Boring No.	Sample Depth (ft)	Blows per ft	Water Content (%)	Liquid Limit	Plastic Limit	Plasticity Index	USCS	Dry Unit Weight (pcf)	% -200 Sieve	Shear Strength (tsf)	Strength Test
B-4	6.5 to 6.8	ref/3"	15								
	8.5 to 8.8	ref/4"	13								
	10.5 to 10.8	ref/3"	13								
	12.5 to 12.7	ref/2"	13	25	16	9					
	14.5 to 14.7	ref/2"	15								
	16.0 to 16.1	ref/1"	21								
	16.1 to 16.6										
B-5	0.0 to 1.5	34	1						8		
	2.5 to 4.0	28	2								
	4.5 to 5.3	50/3"	11								
	6.5 to 6.8	ref/3"	16	23	15	8					
	8.5 to 8.9	ref/4"	13								
	10.5 to 10.9	ref/4"	12								
	12.5 to 12.9	ref/4"	11								
	14.5 to 14.8	ref/3"	10								
	16.5 to 16.7	ref/2"	11								
	18.5 to 18.6	ref/1"	14								
18.6 to 19.1											
B-6	0.0 to 1.5	7	13								
	2.5 to 4.0	10	19	40	16	24					
	4.5 to 6.0	11	19								
	6.5 to 8.0	13	9	23	14	9					
	8.5 to 9.3	50/4"	10								
	10.5 to 10.8	ref/3"	13	23	15	8					
	12.5 to 12.7	ref/2"	15								
	14.5 to 14.7	ref/2"	10								
B-7	0.0 to 1.5	7	1	46	18	28					
	2.5 to 4.0	30	3								
	4.5 to 6.0	14	15						18		
	6.5 to 8.0	18	8								
	8.0 to 8.5										
	8.5 to 8.8	ref/3"	7								
	10.0 to 10.5										
	10.5 to 10.7	ref/2"	8	27	13	14					
	12.0 to 12.5										
	12.5 to 12.6	ref/1"	5								
14.0 to 14.5											

PP = Pocket Penetrometer    TV = Torvane    UC = Unconfined Compression    FV = Field Vane    UU = Unconsolidated Undrained Triaxial  
CU = Consolidated Undrained Triaxial

PROJECT NO. ASA16-016-00

**RABAKISTNER**

FIGURE 11b



# RESULTS OF SOIL SAMPLE ANALYSES

PROJECT NAME: SAWS W-1 Leon Creek Hwy 90 to Hwy 151  
 Upper Segment  
 San Antonio, Texas

FILE NAME: ASA16-016-00 FOR DATA REPORT - NO INVERT ELEVATION.GPJ

1/4/2019

Boring No.	Sample Depth (ft)	Blows per ft	Water Content (%)	Liquid Limit	Plastic Limit	Plasticity Index	USCS	Dry Unit Weight (pcf)	% -200 Sieve	Shear Strength (tsf)	Strength Test
B-7	14.5 to 14.6	ref/1"	6								
	16.0 to 16.5										
	16.5 to 16.6	ref/1"	7								
	18.0 to 18.5										
	18.5 to 18.6	ref/1"	8								
B-8	19.5 to 20.0										
	20.0 to 20.2	ref/2"	7	24	14	10					
	0.0 to 1.5	24	8								
	2.5 to 4.0	30	3								
	4.5 to 6.0	28	4								
	6.5 to 8.0	31	1	27	12	15					
	8.5 to 10.0	21	7						15		
	10.5 to 12.0	14	13								
	12.5 to 13.7	50/8"	7						24		
	14.0 to 14.5										
	14.5 to 14.7	ref/2"	7								
	15.5 to 16.0										
	16.0 to 16.1	ref/1"	7								

PP = Pocket Penetrometer TV = Torvane UC = Unconfined Compression FV = Field Vane UU = Unconsolidated Undrained Triaxial  
 CU = Consolidated Undrained Triaxial

PROJECT NO. ASA16-016-00

# Important Information about This

# Geotechnical-Engineering Report

Subsurface problems are a principal cause of construction delays, cost overruns, claims, and disputes.

While you cannot eliminate all such risks, you can manage them. The following information is provided to help.

## Geotechnical Services Are Performed for Specific Purposes, Persons, and Projects

Geotechnical engineers structure their services to meet the specific needs of their clients. A geotechnical-engineering study conducted for a civil engineer may not fulfill the needs of a constructor — a construction contractor — or even another civil engineer. Because each geotechnical-engineering study is unique, each geotechnical-engineering report is unique, prepared *solely* for the client. No one except you should rely on this geotechnical-engineering report without first conferring with the geotechnical engineer who prepared it. *And no one — not even you — should apply this report for any purpose or project except the one originally contemplated.*

## Read the Full Report

Serious problems have occurred because those relying on a geotechnical-engineering report did not read it all. Do not rely on an executive summary. Do not read selected elements only.

## Geotechnical Engineers Base Each Report on a Unique Set of Project-Specific Factors

Geotechnical engineers consider many unique, project-specific factors when establishing the scope of a study. Typical factors include: the client's goals, objectives, and risk-management preferences; the general nature of the structure involved, its size, and configuration; the location of the structure on the site; and other planned or existing site improvements, such as access roads, parking lots, and underground utilities. Unless the geotechnical engineer who conducted the study specifically indicates otherwise, do not rely on a geotechnical-engineering report that was:

- not prepared for you;
- not prepared for your project;
- not prepared for the specific site explored; or
- completed before important project changes were made.

Typical changes that can erode the reliability of an existing geotechnical-engineering report include those that affect:

- the function of the proposed structure, as when it's changed from a parking garage to an office building, or from a light-industrial plant to a refrigerated warehouse;
- the elevation, configuration, location, orientation, or weight of the proposed structure;
- the composition of the design team; or
- project ownership.

As a general rule, *always* inform your geotechnical engineer of project changes—even minor ones—and request an

assessment of their impact. *Geotechnical engineers cannot accept responsibility or liability for problems that occur because their reports do not consider developments of which they were not informed.*

## Subsurface Conditions Can Change

A geotechnical-engineering report is based on conditions that existed at the time the geotechnical engineer performed the study. *Do not rely on a geotechnical-engineering report whose adequacy may have been affected by:* the passage of time; man-made events, such as construction on or adjacent to the site; or natural events, such as floods, droughts, earthquakes, or groundwater fluctuations. *Contact the geotechnical engineer before applying this report to determine if it is still reliable.* A minor amount of additional testing or analysis could prevent major problems.

## Most Geotechnical Findings Are Professional Opinions

Site exploration identifies subsurface conditions only at those points where subsurface tests are conducted or samples are taken. Geotechnical engineers review field and laboratory data and then apply their professional judgment to render an opinion about subsurface conditions throughout the site. Actual subsurface conditions may differ — sometimes significantly — from those indicated in your report. Retaining the geotechnical engineer who developed your report to provide geotechnical-construction observation is the most effective method of managing the risks associated with unanticipated conditions.

## A Report's Recommendations Are Not Final

Do not overrely on the confirmation-dependent recommendations included in your report. *Confirmation-dependent recommendations are not final*, because geotechnical engineers develop them principally from judgment and opinion. Geotechnical engineers can finalize their recommendations *only* by observing actual subsurface conditions revealed during construction. *The geotechnical engineer who developed your report cannot assume responsibility or liability for the report's confirmation-dependent recommendations if that engineer does not perform the geotechnical-construction observation required to confirm the recommendations' applicability.*

## A Geotechnical-Engineering Report Is Subject to Misinterpretation

Other design-team members' misinterpretation of geotechnical-engineering reports has resulted in costly

problems. Confront that risk by having your geotechnical engineer confer with appropriate members of the design team after submitting the report. Also retain your geotechnical engineer to review pertinent elements of the design team's plans and specifications. Constructors can also misinterpret a geotechnical-engineering report. Confront that risk by having your geotechnical engineer participate in prebid and preconstruction conferences, and by providing geotechnical construction observation.

### **Do Not Redraw the Engineer's Logs**

Geotechnical engineers prepare final boring and testing logs based upon their interpretation of field logs and laboratory data. To prevent errors or omissions, the logs included in a geotechnical-engineering report should *never* be redrawn for inclusion in architectural or other design drawings. Only photographic or electronic reproduction is acceptable, *but recognize that separating logs from the report can elevate risk.*

### **Give Constructors a Complete Report and Guidance**

Some owners and design professionals mistakenly believe they can make constructors liable for unanticipated subsurface conditions by limiting what they provide for bid preparation. To help prevent costly problems, give constructors the complete geotechnical-engineering report, *but* preface it with a clearly written letter of transmittal. In that letter, advise constructors that the report was not prepared for purposes of bid development and that the report's accuracy is limited; encourage them to confer with the geotechnical engineer who prepared the report (a modest fee may be required) and/or to conduct additional study to obtain the specific types of information they need or prefer. A prebid conference can also be valuable. *Be sure constructors have sufficient time* to perform additional study. Only then might you be in a position to give constructors the best information available to you, while requiring them to at least share some of the financial responsibilities stemming from unanticipated conditions.

### **Read Responsibility Provisions Closely**

Some clients, design professionals, and constructors fail to recognize that geotechnical engineering is far less exact than other engineering disciplines. This lack of understanding has created unrealistic expectations that have led to disappointments, claims, and disputes. To help reduce the risk of such outcomes, geotechnical engineers commonly include a variety of explanatory provisions in their reports. Sometimes labeled "limitations," many of these provisions indicate where geotechnical engineers' responsibilities begin and end, to help

others recognize their own responsibilities and risks. *Read these provisions closely.* Ask questions. Your geotechnical engineer should respond fully and frankly.

### **Environmental Concerns Are Not Covered**

The equipment, techniques, and personnel used to perform an *environmental* study differ significantly from those used to perform a *geotechnical* study. For that reason, a geotechnical-engineering report does not usually relate any environmental findings, conclusions, or recommendations; e.g., about the likelihood of encountering underground storage tanks or regulated contaminants. *Unanticipated environmental problems have led to numerous project failures.* If you have not yet obtained your own environmental information, ask your geotechnical consultant for risk-management guidance. *Do not rely on an environmental report prepared for someone else.*

### **Obtain Professional Assistance To Deal with Mold**

Diverse strategies can be applied during building design, construction, operation, and maintenance to prevent significant amounts of mold from growing on indoor surfaces. To be effective, all such strategies should be devised for the *express purpose* of mold prevention, integrated into a comprehensive plan, and executed with diligent oversight by a professional mold-prevention consultant. Because just a small amount of water or moisture can lead to the development of severe mold infestations, many mold-prevention strategies focus on keeping building surfaces dry. While groundwater, water infiltration, and similar issues may have been addressed as part of the geotechnical-engineering study whose findings are conveyed in this report, the geotechnical engineer in charge of this project is not a mold prevention consultant; *none of the services performed in connection with the geotechnical engineer's study were designed or conducted for the purpose of mold prevention. Proper implementation of the recommendations conveyed in this report will not of itself be sufficient to prevent mold from growing in or on the structure involved.*

### **Rely, on Your GBC-Member Geotechnical Engineer for Additional Assistance**

Membership in the Geotechnical Business Council of the Geoprofessional Business Association exposes geotechnical engineers to a wide array of risk-confrontation techniques that can be of genuine benefit for everyone involved with a construction project. Confer with your GBC-Member geotechnical engineer for more information.



8811 Colesville Road/Suite G106, Silver Spring, MD 20910

Telephone: 301/565-2733 Facsimile: 301/589-2017

e-mail: [info@geoprofessional.org](mailto:info@geoprofessional.org) [www.geoprofessional.org](http://www.geoprofessional.org)

Copyright 2015 by Geoprofessional Business Association (GBA). Duplication, reproduction, or copying of this document, or its contents, in whole or in part, by any means whatsoever, is strictly prohibited, except with GBA's specific written permission. Excerpting, quoting, or otherwise extracting wording from this document is permitted only with the express written permission of GBA, and only for purposes of scholarly research or book review. Only members of GBA may use this document as a complement to or as an element of a geotechnical-engineering report. Any other firm, individual, or other entity that so uses this document without being a GBA member could be committing negligent or intentional (fraudulent) misrepresentation.

**ENGINEERING • ENVIRONMENTAL • INFRASTRUCTURE • PROJECT CONTROL**

---

**Austin, TX**

**▶ San Antonio, TX**

**Lake Worth, FL**

**Brownsville, TX**

**Houston, TX**

**Lincoln, NE**

**Dallas, TX**

**McAllen, TX**

**Salt Lake City, UT**

**Freeport, TX**

**New Braunfels, TX**

**Mexico**

---